

ALLOTMENT LETTER

M/S: O2Z Trading and Inductries Pvt. Ltd.

Prop: Ovaice Ishaq Zaroo 5/0.

Mohammad Ishaq Zaroo

R/o. Lake Castle Nigeen Regd.: U74900 JK2011PTC003432

GST Tin: 01AQUPK9755A1ZQ PAN: AQUPK9755A

Adv.Cost: Rs.133.80 lacs (One Crore Thirty Three Lacs Eighty Thoussand only) Allotted Cost: Rs.14693693.00 (Rupees One Crore Forty Six Lacs

Ninety Three Thousand Six Hundred Ninety Three only)

Earnest Money: Rs.50000.00 Time of completion: 180days

Head of account: Under "JJM"

Subject: Allotment for: Construction and successful testing and commissioning of 0.18MGD Rapid Sand

Filtration Plant at Nowpora (Including cost of PST, Clarifloculator, Flash Mixer, Filter House and

wash water disposal chamber) for WSS Rangreth Wavoosa.

Reference: 1. E- NIT No: CE/PHE/Kmr/JSD/132 of 2021-22 Dated. 08-03-2022 issued under endorsement No. CE/PHE/Kmr/JSD/44105-56 Dated. 08-03-2022.

2. UT level committee meeting held on 01-06-2022 under the Chairmanship of Development Commissioner Works PW (R&B).

3. Letter of authorization No. CE/PHE/JJM/8738-82 Dated. 04-06-2022.

4. DJJM meeting notice No. SE/Hyd/Bud/1328-45 Dt. 06-06-2022 along with meeting agenda.

5. District JJM Committee Budgam minutes of meeting held on 07-06-2022 issued vide DDC Budgam's office No. DDCB/Plg/JJM/3187-204 Dated. 22-06-2022.

6. L.O.I No. SE/Hyd/CC/1789-92 Dated. 23-06-2022.

For and on behalf of the Lt. Governor of Jammu & Kashmir UT the contract for above noted work is

fixed with you on the following negotiated rates, terms and conditions:

S. No	Item Description	Qty.	Unit	Rate	Amount
1	Clearing grass and removal of the rubbish upto a distance of 50 m outside the periphery of the area cleared.	1505.000	100 5qm	577.50	8691
2	Earth work in bulk excavation by mechanical means (hydraulic excavator) over areas (exceeding 30 cm in depth, 1.5 m in width as well as 10 sqm on plan) including disposal of excavated earth lead upto 50 meters and lift upto 1.5 m, as directed by Engineer- in-Charge. (All kinds of soil)	715,390	Cum	188.75	135030
2.1	Earth work in bulk excavation by manual means over areas (exceeding 30 cm in depth, 1.5 m in width as well as 10 m2 on plan) including disposal of excavated earth lead upto 50 meters and lift upto 1.5 m, as directed by Engineer-In-Charge. All kinds of soil	126.350	Cum	539.35	68147
3	Extra for every additional lift of 1.5 m or part thereof in excavation/banking excavated or stacked material :All kinds of soil :				
3.1	All kinds of soil :	77.710	Cum	81.65	6345
4	Pumping out water caused by springs, tidal or river seepage, broken water mains or drains and the like.	231.280	1KL	155.55	35976
5	Providing and laying hand packed stone soling 50 mm nominal size including filling, spreading, dressing, ramming, all leads lifts and all carriages complete.	109.240	Cum	1320.00	144197
6	P/L in position cements concrete of specified grade including curing but excluding the cost of centring and shuttering. All work upto plinth level with:				
.1	1:4:8 (1 cement : 4 coarse sand : 8 graded stone aggregate 40mm nominal size)	30.280	Cum	4861.84	147217
.2	1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 40mm nominal size)	33.160	Cum	6434.01	213352





Office of the Executive Engineer, PHE (Jal Shakti) Division Chadoora

ALLOTMENT LETTER

No: PHEDC/ 9606-90

6.3	1:3:6/1	8.250	Cum	5399,02	44542
0.5	1:3:6 (1 cement : 3 coarse sand : 6 graded stone aggregate 40mm nominal size)	0,230	Cum	2022/02	
7	Providing/laying In position specified grade of reinforced cement concrete including curing but excluding the cost of centering, shuttering, finishing and reinforcement. All works upto plinth level				
7.1	1:1%:3 (1 cement : 1% coarse sand : 3 graded stone agg. 20mm nominal size)	29.680	Cum	7800.76	231527
8	Reinforced cement concrete work in walls (any thickness) including attached pilasters, buttresses, plinth and string courses, fillets, columns, pillars, piers, abutments, posts and struts upto floor five level including curing but excluding cost of centering shuttering, finishing and reinforcement.		×		145252
8.1	1:1%:3 (1 cement : 1% coarse sand : 3 graded stone agg. 20mm nominal size)	15.440	Cum	9408.14	145262
9	Providing and laying in position machine batched and machine mixed design mix M-25 grade cement concrete for reinforced cement concrete work, using cement content as per approved design mix, including pumping of concrete to site of laying but excluding the cost of centering, shuttering, finishing and reinforcement, including admixtures in recommended proportions as per IS: 9103 to accelerate, retard setting of concrete, improve workability without impairing strength and durability as per direction of Engineer-incharge. Note: - Cement in this item is @ 330 kg/ cum. Excess or less cement used as per design mix is content considered payable or recoverable separately.				
9.1	All works above plinth level upto floor V level	162,710	Cum	9302.98	1513688
10	Extra for providing richer mixes at all floor levels. Note:- Excess/ less cement over the specified cement content used is payable/ recoverable separately. 5.35.1 Providing M-30 grade concrete instead of M-25 grade BMC/RMC. (Note:- Cement content considered in M-30 is @ 340 kg/cum)	150.920	Cum	111.87	16883
11	Add or deduct for using more or less cement in the items of design mix over and above the specified cement content therein.	160.850	Quint al	1074.37	172812
12	Reinforced cement concrete work in beams, suspended floors, roofs having slope upto 15°, landings, balconies, shelves, chajjas, lintels, bands, plain window sills, staircases and spiral stair cases upto five level including curing but excluding the cost of centring, shuttering, finishing & reinforcement with:				
12.1	1:1%:3 (1 cement : 1% coarse sand : 3 graded stone agg. 20mm nominal size)	56.400	Cum	9849.35	555503
13	Providing and mixing water proofing material in cement concrete work in doses by weight of cement as per manufacturer's specification. (1 kg of water proofing material in 50 kg of cement)	652.500	kgs	57.90	37780
14	Steel reinforcement for R.C.C. work ready to use "cut and bend" rebars of approved make from factory/workshop to construction site including placing in position and binding all complete upto plinth level.				
14.1	Thermo-Mechanically Treated bars of grade Fe-500D or more.	30178.50	Kg	87.18	2630962
15	Centering & shuttering including strutting, propping and removal of form for:	Tagle soon	201210120	200.00	24427
15.1	Foundations, footings, bases of columns etc. for mass concrete.	131.250	sqm	262.30	34427
5.2	Walls (any thickness) including attached pilasters, buttresses, plinth and string courses etc.	1110.690	sqm	573.85	637369
5.3	Suspended floors, roofs, landings, balconies and access platforms.	265.210	sqm	635.60	168567
5.4	Lintel, beams, plinth beams, girders, bressumers and cantilevers.	224.860	sqm	502.85	113071
5.5	Columns, pillars, piers, abutments, posts and struts.	214.350	sqm	680.15	145790
5.6	Stairs (excluding landings) except spiral staircases.	63.090	sqm	807.50	50945
5.7	Extra for shuttering in circular work (20% of respective centring & shuttering items)			J52,45	1292

BAD

114 Page






Office of the Executive Engineer, PHE (Jal Shakti) Division Chadoora

ALLOTMENT LETTER

No: PHEDC/ 9606-90 Dated: 19 - 03 -2023

		Direct			0.0000000000000000000000000000000000000
0/12	Walls (any thickness) including attached pilasters, buttresses, plinth and string	252.120	sqm	114.77	28936
(ii)	courses etc.	17.960	sam	127.12	2283
(222)	Suspended floors, roofs, landings, balconies and access platforms.		sam	100.57	3298
(iii)	Lintel, beams, plinth beams, girders, bressumers and cantilevers.	32.790	RM	242.30	71987
(iv)		297.100	Alvi	-	
15.9	Edges of slabs and breaks in floors and walls Extra for additional height in centering, shuttering where ever required with adequate bracing, propping etc. including cost of de-shuttering and de-centering at all levels, over a height of 3.5 m, for every additional height of 1 meter or part thereof (Plan area to be measured).			267.60	16075
15.10	Suspended floors, roofs, landings, beams and balconies (plan-	60.070	sqm	207.00	157565061-5
16	measured) Brick work with common burnt clay (non-modular) bricks of class designation 7.5 in foundation and plinth including curing in:		Cum	7476.38	188106
200	+ + + + + + + + + + + + + + + + + + +	25,160	Cam		
16.1	Sixten for brick work with common burnt clay bricks/Lement com-	25.160	Cum	1522.20	38299
17	superstructure above plinth level upto floor five level Providing wood work in frames of doors, windows, clerestory windows and other frames, wrought framed and fixed in position with hold fast lugs or with dash fasteners of required dia and length (hold fast lugs or with dash fasteners shall be paid for separately):	1 242	Cum	106894.15	143238
		1.340	Cam	200034125	
18.1	Providing and fixing panelled or panelled and glazed statters for words, windows and clerestory windows fixing with butt hinges of required size with necessary screws, excluding panelling which will be paid for separately, all				*****
	complete as per direction of Engineer-in-charge.	22.680	Sqm	2784.10	63143
19.1	First class kail wood (30 mm thick shutter) P/F fly proof wire gauge to windows & clerestory windows using wire gauge				
20	with average width of aperture 1.4 mm in both directions un complete.	22.670	sqm	925.00	20970
20.1	with Calcariand to S. Wire agong with wire of dia 0.03 mm	22.070	Sqiii	323.00	
21	Steel work welded in built up sections/framed work, including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer using structural steel etc. as required. Chequered plate wherever required all complete.				
21.1	In gratings, frames, guard bar, ladder, railings, brackets, gates and similar	1500.000	Kg	146.63	219945
22	Structural steel work in built up sections, trusses and framed work, including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer all complete for the Installation Testing and Commissioning of Half Bridge with Central Drive mechanism, scrapper and churners for required dia Clarifer.				******
22.1	Welded	3874.640	Kg	102.14	395756
23	Supply/fixing rolling shutters approved make, made of required size M.S. laths, interlocked together through their entire length and jointed together at the end by end locks, mounted on specially designed pipe shaft with brackets, side guides and arrangements for inside and outside locking with push and pull operation				
	complete, including the cost of providing and fixing necessary 27.5 cm long wire springs manufactured from high tensile steel wire adequate strength confirming to IS:4454 port-1 and M.S. top cover of required thickness for rolling shutters	24 1	9		

12 | Page





Office of the Executive Engineer, PHE (Jal Shakti) Division Chadoora

ALLOTMENT LETTER

		2,000	No.	483.10	966
22.2	Providing and fixing ball bearing for rolling shutters.	2.000	740.		
23.2	Providing and fixing ball bearing for rolling shutters. Cement concrete flooring 1:2:4 (1cement: 2 coarse sand: 4 graded stone aggregate) finished with a floating coat of neat cement including cement slurry and curing complete, but excluding the cost of nosing of steps etc.				
521	complete	161.310	sqm	505.00	81462
24.1	50 mm thick with 20mm nominal size stone aggregate.				
25	Providing and laying Ceramic glazed floor tiles 3000000000000000000000000000000000000	-			00220
CATA TA	In colour such as White, Ivory, Grey, Fume, Red Brown (as dirrected by the	79.560	sqm	1210.66	96320
25.1	engineer incharge) in a thickness as per sample of marble				
26	engineer incharge) Flooring with marble stone of specified thickness as per sample of marble approved by Engineer-in-charge, over 20 mm (average) thick base of cement approved by Engineer-in-charge, over 20 mm (average) thick base of cement slurry mortar 1:4 (1 cement:4 coarse sand) laid and jointed with grey cement slurry mortar 1:4 (1 cement:4 coarse sand) laid and jointed with grey cement slurry mortar 1:4 (1 cement:4 coarse sand) laid and jointed with grey cement slurry mortar 1:4 (1 cement:4 coarse sand) laid and jointed with grey cement slurry mortar 1:4 (1 cement:4 coarse sand) laid and jointed with grey cement slurry mortar 1:4 (1 cement:4 coarse sand) laid and jointed with grey cement slurry mortar 1:4 (1 cement:4 coarse sand) laid and jointed with grey cement slurry mortar 1:4 (1 cement:4 coarse sand) laid and jointed with grey cement slurry mortar 1:4 (1 cement:4 coarse sand) laid and jointed with grey cement slurry mortar 1:4 (1 cement:4 coarse sand) laid and jointed with grey cement slurry mortar 1:4 (1 cement:4 coarse sand) laid and jointed with grey cement slurry mortar 1:4 (1 cement:4 coarse sand) laid and jointed with grey cement slurry mortar 1:4 (1 cement:4 coarse sand) laid and jointed with grey cement slurry mortar 1:4 (1 cement:4 coarse sand) laid and jointed with grey cement slurry mortar 1:4 (1 cement:4 coarse sand) laid and jointed with grey cement slurry mortar 1:4 (1 cement:4 coarse sand) laid and jointed with grey cement slurry mortar 1:4 (1 cement:4 coarse sand) laid and jointed with grey cement slurry mortar 1:4 (1 cement:4 coarse sand) laid and jointed with grey cement slurry mortar 1:4 (1 cemen		92		474401
	mortar 1:4 (1 cement:4 coarse sand) tale unit jointed in the jointed and curing complete with: including skirting in vertical, rubbing, polishing and curing complete with:	76.350	sqm	6175.39	471491
261		17,800	sqm	579.31	10312
26.1	Extra for pre finished nosing to treads of steps of marble stone Extra for pre finished nosing to treads of steps of marble stone Extra for pre finished nosing to treads of steps of marble stone	27,140	T-12		
26.2	Extra for pre finished nosing to treads of steps of metals. State Filling available excavated earth (excluding rock) in trenches, plinth, sides of foundations etc. in layers not exceeding 20 cm in depth, consolidating each deposited layer by ramming and watering, lead upto 50 m and lift upto 1.5	579,580	Cum	198.70	115163
	m. Supplying and filling in plinth with fine sand under floors including, watering,	9.870	Cum	787.40	7772
28					
29	ramming, consolidating and dressing complete: 12mm Cement plaster finished with a floating coat of neat cement of mix:	2095.340	sam	343.75	720273
29.1	4 - 3 / 1 coment : 3 fine sand)	363,430	sqm	278.60	101252
29.2	15mm thick on brick work 1: 6 (1 cement: 6 fine sund)	457.960	sqm	221.50	101438
29.3	6mm thick 1 : 3 (1 cement : 3 fine sand) plain	4371300			
30	4 1 4 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1		7	SMINOLES	5044
30.1	With ready mixed pink or grey primer of approved brand and managette.	116.700	sqm	59.50	6944
31	Painting with synthetic enamel paint of approved brand and munificative to				A Section 6.5
31.1	Two or more coats on new work over an under coat of suitable shade with	116.700	sqm	179.80	20983
32	Finishing walls with water proofing cement paint of required shade on New	820.310	sqm	91.80	75304
33	Finishing with Epoxy paint (two or more coats) at all locations prepared and applied as per manufacturer's specifications including appropriate priming coat, preparation of surface, etc complete	200 000	- Salar	188.80	37760
33.1	On steel work	200.000	sqm	100.00	37700
34	Distempering with dry distemper of approved brand & manufacture (two or more coats) and of required shade on new work, over and including water thinnable priming coat to give an even shade	307.610	sqm	115.45	35514
35	Distempering with oil bound washable distemper of approved brand and manufacture to give an even shade on New work (two or more coats) over and including priming coat with water thinnable cement primer.	307.610	sqm	149.05	45849





Office of the Executive Engineer, PHE (Jal Shakti) Division Chadoora

ALLOTMENT LETTER

	71.17.44				
TO NAME	Providing and applying white cement based putty of specified thickness, of	,			
36	approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete.	615.230	sqm	172.40	106066
36.1		-			
37	Providing/fixing hand rail of approved size by welding etc. to steel room railing, balcony railing, staircase railing and similar works, including applying				71373
25.00	priming coat of approved steel primer.	412.800	Kg	172.90	12373
37.1					
38	M.S. tube Providing and fixing aluminum handles ISI marked anodized (anodic coating not less than grade AC 10 as per IS: 1868) transparent or dyed to required			65.26	332
153111	colour and shade with necessary screws etc.complete	5.000	each	66.35	2092
38.1	125 mm	40.000	each	52.30	2032
38.2		755-55-5-5		560860	2227
39	Providing and fixing aluminum tower bolts ISI marked anodized (anodic coating nat less than grade AC 10 as per IS: 1868) transparent or dyed to	5,000	each	80.38	402
-	required colour or shade with necessary screws etc. complete: 150x10 mm	80.000	each	57.25	4580
39.1	100x10 mm				
40	100x10 mm Providing corrugated G. S. sheet roofing including vertical/curved surface fixed with polymer coated J or L hooks, bolts and nuts 8mm diameter with bitumen and G.I limpet washers or with G.I. limpet washers filled with white lead, including a coat of approved steel primer and two coats of approved paint on overlapping of sheets complete (upto any pitch in horizontal/vertical or curved surface)excluding the cost of purlins, rafters and trusses and			830.25	91112
	Including cutting to size and shape wherever required.	109.740	sam	830.25	34442
40.1	0.50 mm thick with zinc coating not less than 275 gram/m2 Providing ridges or hips of width 60cm overall width plain G.S sheets fixed				
41	with polymer coated J. or L hooks, boits and had omin				*
	bitumen washers complete	37.800	Mtr	691.35	26133
41.1	0.63 mm thick with zinc coating not less than 275 gram/m2				
42	Providing and fixing plained eaves boarding. 2nd class kan viola	44.050	Mtr	693.90	30566
42.1	PART PART		17.	c00.00	19824
43	Providing and fixing of 0.5mm Color GS Sheet Soffit boarding including Backing, supports etc complete job	33,040	Mtr	600.00	15024
44	Providing and fixing glazing in aluminum door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineerin-charge. (Cost of aluminum snap beading shall be paid in basic item.)			0000	
44.1	With floating glass panes of 4.0 mm thickness (weight not less than 10.00 kg /	20.000	sqm	1072.17	21443
45	Providing & fixing of PVC under drainage laterals with specifications conforming to IS-4985 & IS-15801, 8mm thick fabricated out of approved make with nominal dia of 9mm perforations as per design of bed provided at 60 degrees along with PVC Tees and end caps grouted in concrete, the pressure rating of 10kg/sq cm				
5.1	75 mm dia	80.000	Mtr	1420.00	113600
46	Electrical Items:Supplying and fixing of 25mm dia. medium class PVC conduit along with accessories in surface/recess including cutting the wall and making good the same in case of recessed conduit as required.	100.000	Mtc	103.50	10350

14 | Page





Office of the Executive Engineer, PHE (Jal Shakti) Division Chadoora

ALLOTMENT LETTER

No: PHEDC/ 9686-90 Dated: 19 - 03 -2023

		Dated:	19 -0	2 -2023	
47	Providing/carrying out wiring for light point/ fan point/ exhaust fan point/ call bell point with 1.5 sq.mm FRLS PVC insulated copper conductor single core cable in surface / recessed medium class PVC conduit, with modular switch, modular plate, suitable GI box and earthing the point with 1.5 sq.mm FRLS PVC insulated copper conductor single core cable as required. (excl. cost of conduit)	12.000	No	824.55	9895
48	Providing and carrying out wiring for twin control light point with 1.5 sq.mm FRLS PVC insulated copper conductor single core cable in surface / recessed medium class PVC conduit, 2-way modular switch, modular plate, suitable GI box and earthing the point with 1.5 sq.mm FRLS PVC insulated copper conductor single core cable etc. as required. (excl cast of conduit)	12.000	No	1215.55	14587
49	Providing and carrying out wiring for heating points with 4.0 sq.mm FRLS PVC insulated copper conductor single core cable in surface / recessed medium class PVC conduit, modular combined S&S 16Amp along with modular plate, suitable GI box and earthing the point with 2 sq.mm FRLS PVC insulated copper conductor single core cable etc. as required. (excl cost of conduit)	12.000	No	1300.00	15600
50	Supply of 1200 mm sweep Ceiling Fans complete in all respects. Confirming to relevant Indian Standards	3.000	No.	2125.00	6375
51	Supply of 200 mm nominal sweep Exhaust Fans Including shutter from outside complete Confirming to relevant Indian Standards	4.000	No.	1550.00	6200
52	Supplying and fixing suitable size Gi box with modular plate and cover in front on surface or in recess, including providing and fixing 6 pin 5/6A & 15/16 A modular socket outlet and 15/16 A modular switch, connections etc. as required.	3.000	No.	569.25	1708
53	Supply and fixing of two module stepped type Electronic Fan regulator on the existing modular plate switch box including connections but excl cast modular plate etc., as required.	3.000	No.	393.30	1180
54	Supply of 24-Watt LED slim aluminum panel surface type complete all respects.	3.000	No.	600.00	1800
55	Supplying and fixing 12-way double door, single pole and neutral, sheet steel, MCB distribution board, 240 V, on surface/ recess, complete with tinned copper bus bar, neutral bus bar, earth bar, din bar, interconnections, powder painted including earthing etc. as required. (But without MCB/RCCB/Isolator)	3.000	No.	2360.95	7083
56	Providing, fitting/testing of LED flood light IP65 30W rating to pre-wired electric points on the outside of the Filter House building.	8.000	No.	1500.00	12000
57	Providing and laying of armoured cable 95mm, 3.5 core for main service line of reputed make in P.V.C pipes of required dia to accommodate the service line including bends etc., from main transformer to the main panel board including copper thimbles, earth work excavation and filling for laying of cable complete.	70.000	Mtr	325.00	22750
58	Providing and fitting at site 3-phase, Voltage stabilizer of following ratings, oil emersed, of standard make and quality including accessories as required. The job includes making of connections with main panel board and service line. To be paid in fitted and finished form after testing on full load capacity, complete job.				
58.1	25 KVA	1.000	No	42000.00	42000
59	Providing/fitting of panel board with angle iron supports and A.C. sheets for fixing of MCCB, change over switch, bus bars etc. The job includes nuts bolts and embedding of supports in cement concrete blacks complete job.	2.000	No	4250.00	8500
60	Providing and fitting of:				
0.1	64 Amp. 4 pole Change over of reputed make	2.000	No	25000.00	10000
50.2	64 Amp-Copper bus bar	2.000	No	3750.00	7500

8240

15 | Page





Office of the Executive Engineer, PHE (Jal Shakti) Division Chadoora

ALLOTMENT LETTER

	al 86-70
No: PHEDC/	1000
100.11.	13 2023

			Ale	2700.00	8100
22.2	CO ACULANCES	3.000	No	1250.00	3750
50.3	63 Amp MCCB	3.000	No No	445.00	1335
50.4	16 Amp MCCB	3,000	No	1190.00	4760
60.5	3-phase indicator points	4.000	NO		
60,6	3-phase voltmeter and Amperemeters Providing, fitting, testing and commissioning of following itemn for Alum			197	
61	Providing, fitting, testing and commissioning by year	4.000	Set	2500.00	2500
-	Dosing Unit-	1.000	500		
62	Mixing device with reduction gear system.	2,000	No	4800.00	9600
62.I	Mixing device with reduction gear system	1.000	No	4548.00	4548
62.2	1,0 HP	1.000	No	1680.00	1680
62.3	Foundation \ Base plate	1.000			
62.4	Starter along with necessary wiring upto motor Starter along with necessary wiring upto motor Providing, fitting, testing and commissioning of following items for Alum		1		
63	Providing, fitting, testing and commissions	1.000	No	2500.00	2500
. Charles	Dosing Unit-	1,000			
63.01	Mixing device with reduction gear system.	2.000	No	4800.00	9500
63.02	3-phase electrically driven motors:		No	4548.00	4548
63.03	1.0 HP	1.000	No	1680.00	1680
63.04	Foundation / Base plate.	1.000	No	530.00	530
63.05	Starter along with necessary wiring upto motor P.V.C outlet, overflow system with fittings upto point of application	1.000	No	1350.00	1350
63.06	P.V.C outlet, overflow system with fittings up to p	1.000	No	530.00	530
63.07	150 mm dia Drain out let	1.000	1	1500.00	1500
63.08	50mm dia service water piping	1.000	No	10000.00	10000
53.09	Constant dozing unit with time device.	1,000	No	10000.00	
63.10	Manually operated hoist Providing, fitting, testing and commissioning of following items for Chlorine			1 1	
64	Posing Unit-	1.000	Set	2500.00	2500
64.1	Mixing device with reduction gear system.				
64.2	3-phase electrically driven motors:	2.000	No	4800.00	9600
64.3	1,0 HP	1.000	Set	4548.00	4548
64.4	Foundation / Bose plate,	1.000	Lot	530.00	530
64.5	P.V.C outlet, overflow system with fittings upto point of application	1.000	No	1680.00	1680
64.6	Starter along with necessary wiring upto motor	1.000	Lot	1350.00	1350
64.7	150 mm dia Drain out let	1.000	Lot	530.00	530
64.8	50mm dia service water piping	1.000	Set	1500.00	1500
64.9	Constant dozing unit with time device.	2.000			
65	Providing fitting, testing and comissioning of air blower standard make ISI mark capable of providing compression @ 0.35 kgs/sqcm coupled with suitable 3 phase induction electric motor complete with auxiliary pipe system upto filter beds with pressure guage, Nozzles, foundation block, base plate, air check valve, non- return valve, Starter etc			0750000	175000
55.1	4.20 KLPM Air blower with 5.0 HP Motor.	2.000	No	87500.00	1/5000
66	Supply installation and successful testing and commissioning of mono block pumping unit standard make ISI mark coupled with 2 phase induction motor with appropriate pumping capacity so as to fill the tank within the max. of 2 hours with nominal dynamic head of 25m along with all accessories like foot valves, non-return valves, foundation block, base plate, suction pipe, suitable rising main with nominal dia 50mm (class-B) with heavey duty valves and other accessories required for the job.		7		l le

16 | Page





Office of the Executive Engineer, PHE (Jal Shakti) Division Chadoora

ALLOTMENT LETTER

No: PHEDC/ 9686-90
Dated: 19 -03 -2023

		2,000	No	20268.00	40536
66.1	Pumping unit with 5.0 HP Motor.	2.000	110		
67	Pr/fixing, installation, successful commissioning of double flanged his pipes, specials to be fabricated from MS tube heavy quality nominal thickness 6mm, conforming to relevant Indian Standard IS-1239 and/or IS 1161 read with up to date omendments. The pipe material should be of standard quality and must withstand all anticipated design pressure ratings. The work should be leakproof withstand all anticipated design pressure ratings.	1500.000	Kg	147.00	220500
	and should be pointed with anti corrosive rea under with rubber insertions,				
68	and should be painted with anti corrosive real by department. Pr/flxing D.I. sluice valves Class 1 (with cap) complete with rubber insertions, bolts, nuts, extention rod, joint connector, supporting pedestal with base plate, top plate and necessary anchoring bolts etc. (the tall pieces if required will be paid separately). Confirming IS:14846 read with latest amendments.	3.000	No	14058.00	42174
	will be paid separately). Conjuning 15.2 15.1	6.000	No	17210.00	103260
68.1	80 mm dia.	8.000	No	26720.00	213760
68.2	100 mm dia.	2.000	No	42300.00	84600
68.3	150 mm dia.	1.000	No	66440.00	66440
68.4	200 mm dia.	1.000	No	83100.00	83100
68.5	250 mm dia.	1.000			
68.6 69	300 mm dia. P/F testing and commissioning of MS Rotating Desludging Bridge comprising				
69.1	of following items: Structural steel work in built up sections, trusses and framed work, including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer all complete.	2200,000	Кд	102.14	224708
		2.000	No	4800.00	9600
69.2		2.000			
69.4	Peripheral drive assembly with Johnwing motors, g	* 000	No	24268.00	24268
LAIDEAIN .	(60:1 reduction gear box). Pumping unit with 5.0 HP Motor.	1.000	No	1680.00	1680
69.5		1.000	110	2220,5	
69.6 69.7	Starter along with necessary wiring upto motor Flocculator drives assembly with crown wheel, pinion sets, reduction gear (40:1) with motors complete job.		Ma	7300.00	7300
	7.7.7.12	1.000	No	6500.00	6500
69.8	1.0 HP Incoming cable, telescopic electric pole with rotary current collector	1.000	No	6500.00	3300
69.9 70	Providing and laying/fixing S&S Centrifugally Cast (Spun)/ Ductile Iron Pipes Class K-7 conforming to IS: 8328				2540
-	100 mm dia	6.000	Mtr	1108.15	6649
70.1	150 mm dia	6.000	Mtr	1581.25	9488
70.2	200 mm dia	155.000	Mtr	1947.00	301785
70.3	250 mm dia	6.000	Mtr	2504.80	15029
70.4	300 mm dia	6.000	Mtr	3129.20	18775
70.5 71	Providing and laying D.I. standard specials such as tees, bends, collars, tapers, caps etc. sultable for flanged jointing as per 15: 9523 (as per site requirement)				
77.7	Up to 300 mm dia.	1.000	Qtl	7823.70	7824
71.1	Providing and fixing G.I. pipes (B medium) complete with G.I. fittings				
72					
72	excluding trenching and refilling etc. (external work) 20 mm dia. nominal bore	12.000	Mtr	204.45	2453

A STATE OF THE STA

17 | Page





Office of the Executive Engineer, PHE (Jal Shakti) Division Chadoora

ALLOTMENT LETTER

No: PHEDC/ 9606-10

		Datea:	1/	V -2023	40.00
22.2	50 mm dia naminal hara	12,000	Mtr	559.35	6712
2.3	50 mm dia. nominal bore	12.000	Mtr	711.70	8540
2.4	65 mm dia. nominal bore	12.000	Mtr	840.00	10080
72.5	80 mm dia. nominal bore	12.000	Mtr	1234.95	14819
72.6	100 mm dia. nominal bore				
73	Providing/fixing of MS flanged joints (12mm thick) to double flanged GI/DI pipes including cutting of pipes, welding charges, cutting of flanges, rubber pipes including cutting of pipes, welding charges Complete Job.			4400.00	4400
	gasket, bolts, nuts including testing of joint & all carriages Complete Job.	4.000	No	1100.00	9120
73.1	80 mm dia. pipe	6.000	, No	1520.00	12900
73.2	100 mm dia. pipe	6.000	No	2150.00	13920
73.3	150 mm dia. pipe	4.000	No	3480.00	15420
73.4	200 mm dia, pipe	2.000	No	7710.00	15420
73.5	300 mm dia. pipe	90.000	sqm	800.00	72000
74	300 mm dia. pipe Providing & fixing of 0.63mm thick PGI sheets at construction joints including all leads and lifts complete job as directed by Engineer-in-charge Gravel (Graded gravel)	90.000	34,		25225
75	all leads and lifts complete job as directed by Engineer in Active Graded gravel - Supply and filling of filter media from approved source - Gravel (Graded gravel - size ranging from 2.0mm to 40.00 mm) in filter beds. Including all carriages,	4.680	Cum	7700.00	36036
	complete job Supply 8, filling of filter media from approved source - Sand (Coarse filter sand -	7.020	Cum	7968.00	55935
75	in filter beds. Including all carriages, complete job	TOWNS SET		1 1	
	Carriage of materials by mechanical transport medaling				97880
77	stacking of materials - SAND:	279.800	Cum	349.82	97000
77.1	stacking of materials - SAND: Sand from Shilvot Shadipara to site of work for an average lead of 26 Kms.			8	
78	Carriage of materials by mechanical transport including	373.600	Cum	349.82	130693
78.1		57510-			
79	Carriage of materials by mechanical transport metals	64.530	Cum	380.28	24536
		64.520	Cum	300.20	
79.1	Carriage of materials by mechanical transport including to				C0753
	stacking of materials - Cement/Steel: Cement/Steel from Chadoara to site of work for an average lead of 10 Kms.	316.700	Ton	217.09	68752
80.1 81	Carriage of materials by mechanical transport including loading, and and				
81.1	stacking of materials - Bricks: Bricks from Budgam to site of work for an average lead of 11 Kms.	11951.00	1000 No	670.00	8007
Nell Secret	51900 (2009)				
82.1	Applying priming coat: With ready mixed red oxide Zinc Chromate primer of approved brand and	150.000	sqm	52.75	7913
82.2	manufacture on steel galvanized Iron/steel works With ready mixed red oxide Zinc Chromate primer of approved brand and	150.000	sqm	28.90	4335
83	monufacture on steel work (second coot) Providing push-on-joints to Centrifugally (Spun) Cast Iron Pipes or Ductile Iron Pipes including testing of joints and including the cost of rubber gasket: 80mm dia pipes	40.00	No	213.00	8520
84	Providing and applying of swellable type water stop tape, 19mm x 25mm thick in linear meter (expansive nature) for construction joints treatment of RCC structure such as raft slab, retaining walls, water storage tank and at the junctions of raft slab with the retaining walls etc After cleaning the surface, one coat of required primer for swellable water stop tape shall be applied throughout the length of the	21.660	RM	547.60	11861

MAN OF THE PROPERTY OF THE PRO

EXEN Eng.

18 | Page





Office of the Executive Engineer, PHE (Jal Shakti) Division Chadoora

ALLOTMENT LETTER

	a II. Ame	Angel and the same	17-1		
	joint @3.78 litre per 240 running meter. Over the primed surface swellable type water stop tape shall be placed. The work shall be carried out all complete as per specification and the direction of the Engineer-In-Charge. The product performance shall carry guarantee for 10 years against any leakage				
85	Providing and fixing aluminum work for abors, which will be sections and other with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixed with dash sections of approved make conforming to IS: 733 and IS: 1285, fixed with dash sections of approved make conforming to IS: 733 and IS: 1285, fixed with dash sections of approved dash and size including necessary filling up of gaps at junctions fastener of required dia and size including necessary filling up of gaps at junctions fastener of required dia and size including recessary filling up of gaps at junctions fastener of required dia and size including clean states. Aluminum snap beading for methanically wherever required including clean angle, Aluminum snap beading for methanically wherever required including clean angle, Aluminum snap beading for methanically wherever required including clean angle, Aluminum snap beading for methanically wherever required including clean angle, Aluminum snap beading for methanically wherever required including clean angle, Aluminum snap beading for methanically wherever required including clean angle, Aluminum snap beading for methanically wherever required including clean angle, Aluminum snap beading for methanically wherever required including clean angle, and angle and angle and angle and angle and angle angle and angle ang				
	architectural drawings and the business		Кд	449.85	89970
	and dash fasteners to be paid for separately). and dash fasteners to be paid for separately).	200,000		535.35	54606
85.1	Powder coated aluminum (minimum annum thickness of powder	102.000	Kg	333.33	13861287-050
85.2	Powder coated distributions coated 50 microns) Providing and fixing 12mm thick prelaminated particle board flat Providing and fixing 12mm thick prelaminated particle board for IS:				17162
86	pressed three layer or graded in aluminum doors, windows 12823 Grade-I type-II) in panelling fixed in aluminum doors, windows 12823 Grade-I type-II) in panelling fixed in aluminum doors, windows 12823 Grade-I type-II) in panelling fixed in aluminum doors, windows 12823 Grade-I type-II) in panelling state of the layer of the laye	15.000	sqm	1144.10	17102
87	complete as per architectural drawings and directions of pre-lominated particle board with decorative lamination on both sides. Pre-lominated particle board with decorative lamination on both sides. Providing and fixing double action hydraulic floar spring of approved brand and manufacture IS: 6315 marked, having brand logo embossed brand and manufacture IS: 6315 marked, having brand logo embossed on the body/plate with double spring mechanism and door weight upto 125 kg on the body/plate with double spring mechanism and door weight upto 125 kg on the body/plate with double spring mechanism and door weight upto 125 kg on the body/plate with double spring mechanism and door weight upto 125 kg on the body/plate with double spring mechanism and door weight upto 125 kg on the body/plate with double spring mechanism and door weight upto 125 kg on the body/plate with double spring mechanism and door weight upto 125 kg on the body/plate with double spring mechanism and door weight upto 125 kg on the body/plate with double spring mechanism and door weight upto 125 kg on the body/plate with double spring mechanism and door weight upto 125 kg on the body/plate with double spring mechanism and door weight upto 125 kg on the body/plate with double spring mechanism and door weight upto 125 kg on the body/plate with double spring mechanism and door weight upto 125 kg on the body/plate with double spring mechanism and door weight upto 125 kg on the body/plate with door weight upto 125 kg on the body/plate with door weight upto 125 kg on the body/plate with door weight upto 125 kg on the body/plate with door weight upto 125 kg on the body/plate with door weight upto 125 kg on the body/plate with door weight upto 125 kg on the body/plate with door weight upto 125 kg on the body/plate with door weight upto 125 kg on the body/plate with door weight upto 125 kg on the body/plate with door weight upto 125 kg on the body/plate with door weight upto 125 kg on the body/plate with door weight upto 125 kg on the body/plate with door wei	2.000	No	2370.70	4741
	direction of Engineer-in-charge: With Stantes		-	Total:	1360527
	mm thickness	100000	100		108842
	Add 8% above on all iten	ns as per n	egotiati	Total:	1469369
				Total:	1403303

NOTE:

The work for construction of Filtration Plant for WSS Kultreh Wanpora has been advertised at a cost of Rs.133.80 lacs, after receiving the approved design from the Worhty Chief Engineer some minor changes in quantities were made accordingly the basic amount also got changed from Rs.133.80 lacs to Rs.136.05 lacs.

(Rates & quantity checked)

a Draftsman

Executive Engineer PHE (Jal Shakti) Division Chadoora

19 | Page

Terms Conditions

1. The cost of work shall in no case exceed to allot amount.

2. Earnest Money Rs. 50000/-pledged to Financial Advisor / Chief Accounts Officer Kmr, Jal Shakti (PHE) Department Srinagar.

3. Time of completion is essence of the contract.

4. The work shall have to be started by you at site immediately and ensure its successful completion within a period of 180 days from the date of issuance of LOI/Allotment from this office strictly in accordance with the approved proposals falling which the work shall have to be got executed through any other means at your risk and cost, besides CDR deposited by you as security against this contract shall be recommended for forfeiting.

5. An agreement shall have to be drawn by you with the department within a period of 07 days from the date of issuance of allotment, failure to execute such a formal deed shall not however prevent

the contract from being enforced upon you.

6. The allotted work shall be subject to check by the third party monitoring agency appointed by the department.

7. Payment shall be released as per actual / measured work done not less than 20% of the allotted

cost on a monthly basis.

8. Performance security equivalent to 3% of the value of the contract shall have to be deposited by you in shape of CDR/FDR/Bank Guarantee within one week of issuance of allotment order and valid for a period of 3 months beyond the expiry of warranty period of the contract.

9. The firm shall be bound for satisfactory performance of work for 18 months after the successful commissioning of the work. If during warranty period any malfunctioning / defects arise, you shall have to rectify same within a period of 10 days of receipt of intimation. In case of any failure on your part, the department may get the defects removed / repaired by any other means and cost thereof shall be recovered from you and shall be recommended for further punitive action as governed under the relevant clause of the contract including black listing.

10. Pre & post Geo-tagged photographic evidence be taken during the execution of the work and

shall have to be produced at the time of submission of the bill.

11. The quantity allotted shall have to be executed on ground strictly as per the estimates that have been framed in the DPR.

12. All other terms and conditions shall be applicable as laid down in standard bid document and PWD from No. 25/33.

13. Any rule / terms and conditions if not stipulated in the bidding documents, shall be strictly dealt in accordance with the relevant rules / guidelines stipulated in General Financial Rules (GFR-2017) and manual for procurement of works 2019 G.O.I.

14. COR No. 3126342 deled: 29/3/2020 Rs. 50,000/2

Executive Engineer, Jal Shakli PHE Division G Chadoora

Copy to the:

Chief Engineer, Kashmir Jal Shakti PHE Department Srinagar for favour of information.

2. District Development Commissioner Budgam (Chairperson DJJM) for favour of information.

3. Superintending Engineer Hydraulic Circle Budgam (Member Secretary DJJM) for favour of information.

4. Assit. Ex. Engineer Jal Shakti PHE Sub-Division for Information and necessary action. He shall ensure execution of work as per JJM guidelines, monitoring by TPIMA, and observance of all relevant IS codes and Government Orders in vogue.