Government of Jammu & Kashmir Office of the Executive Engineer, PHE (Jal Shakti) Division Chadoora

ALLOTMENT LETTER (JJM)

No: PHEDC/ 5343-44. Dated: 13 - 10 -2022

Mohammad Yousuf Paul M/S:

S/o: Ab Karim Paul

R/o: Ganjibagh Chadoora

Regd: SE/Hyd/Sopore/AYY/2004-05

GST Tin: 01AQDPP4948B1Z7

Pan No: AQDPP4948B

Reference:

Adv.Cost: Rs.134.06 lac (One Crore Thirty Four lacs Six Thousand only)

Allotted Cost: Rs.13405772.00 (Rupees One Crore Thirty Four Lacs

Five Thousand Seven Hundred Seventy Two only)

Earnest Money: Rs.268120.00

Head of account: Jal Jeevan Mission (JJM)

Allotment for: Laying/fitting of pipes including De-silting/stone pitching of IR at Mono for WSS Subject:

SOIWARD BATAPORA.

Your tender in response to this office e-NIT No: 04/PHEDC of 04/2022 (2022-23) issued vide 1.

endorsement No: PHEDC/284-95 Dated. 19-04-2022. Chief Engineer, Kmr. Jal Shakti PHE Department Srinagar's No. CE/PHE/MC/DB/13745-83 2.

Dated. 26-07-2022. District Dev. Commissioner, Budgam's Authorization No. 6027-47 Dated 01.08.2022. 3.

Superintending Eng., Hyd. Circle Budgam's No. SE/Hyd/Bud/2640-42 Dated 01-08-2022.

4. This office L.O.I No. PHEDC/3329-36 Dated. 04-08-2022. 5.

For and on behalf of the Lt Governor of Jammu & Kashmir UT the contract for above noted work is fixed

with you on the following quoted rates, terms and conditions:

	with you on the following quoted rates, terms and conditions:	Qty.	Unit	Rate	Amount
T	Home of Work				
10	arth work in excavation by manual means in trenches for foundations, drains, pipes, ables etc. (not exceeding 1.5 m in width) and for shafts, wells, cesspits and the like not exceeding 10 sam on plan, including dressing of sides and ramming of bottoms lift upto 1.5 m, including getting out excavated earth and disposal of surplus excavated	4025.56	Cum	436.00	1755144.16
1	earth as directed: All kinds of Soil	1000.39	Cum	646.05	646301.96
,	Metalled Surface plinth, sides of			VVIII V	***********
	Filling available excavated earth (excluding fock) foundations etc. In layers not exceeding 20 cm in depth, consolidating each deposited	4528.75	Cum	198.70	899862.63
+	foundations etc. In layers not exceeding 20 of and lift upto 1.5 m. layer by ramming and watering, lead upto 50 m and lift upto 1.5 m. Providing / fixing of ISI make sluice valve including all carriages upto site of work including cost of tail pieces, nuts bolts, MS flanges complete job (Kirloskar or Zolto	2.00	No	30000.00	60000.00
4	make): 150 mm dia sluice valve	5.00	No	20000.00	100000.00
5				* * * * * * * * * * * * * * * * * * * *	66544.05
6	100 mm dia sluice valve Laying in position Ductile Iron S&S PIPES (excluding cost of pipe).	271.00	Qtl	245.55	66344.03
7	100 mm dia Ductile Iron Class K - 7 Fipes				
8	Providing push-on-joints to Centrifugury (specific including testing of joints and including the cost of rubber gasket	364.00	No	89.70	32650.80
9	100 mm dia pipes Laying and fitting of G.I. pipes (all classes) complete excluding cost of pipes, fittings	3000.00	'Rm	73.05	219150.00
10	and Earth work: 65 mm dia G.I pipes	4500.00	Rm	40.80	183600.00
	50 mm dia G.I pipe	3000.00	Rm	40.80	122400.00
11	40 mm dia G.I pipes	400.00	Rm	30.65	12260.00
12	25 mm dia G.1 pipes	3000.00	Rm	20.25	60750.00
13	20 mm dia G.I pipes	3000,00		666.25	129918.75
14	20 mm dia G.I pipes 20 mm dia G.I pipes Making connection of GI distribution branch with G.I main of following sizes by P/F Making connection of GI distribution branch with G.I main of following sizes by P/F	195.00	No	401 A 201 C 111 C 40	7219.95
15	Making connection of GI distribution branch with G.: main of form nominal bore Tee, including cutting & threading the pipe etc. complete: 15 to 40mm nominal bore Tee, including cutting & threading the pipe etc. complete: 15 to 40mm nominal bore	3.00	Each	2406.65	4713.75
16	tal auto valve with C.I White of opposit	5.00	Each	942.75	4723.70
17					

Drawing Branch

Government of Jammu & Kashmir Office of the Executive Engineer, PHE (Jal Shakti) Division Chadoora ALLOTMENT LETTER (JJM)

No: PHEDC/ 5343-44 Dated: -2022 40 mm dia 6.00 Each 617.80 18 3706.80 Carriage of pipes by Mechnical transport from different source upto dumping site of 2000.00 9.20 Mtr 18400.00 19 work including loading, un-loading & stacking lead 30 Kms: 100 mm dia D.I pipe M.T 387.87 13.50 5236.25 20 65 mm dia G.I pipe M.T 387.87 18.81 7295.83 21 50 mm dia G.I pipe M.T 387.87 9.75 3781.73 40 mm dia G.I pipe 22 387.87 M.T 310.30 0.80 25 mm dia G.I pipe 23 4.26 M.T 387.87 1652.33 24 20 mm dia G.I pipe Carriage of pipes from Dumping site to actual site of work by manual labour / ponies 13.64 27280.00 2000.00 Mtr 25 including handling/rehandling complete lead 1000 mtrs: 100 mm dia D.I pipe 13.50 M.T 504.90 6816.15 26 65 mm dia G.I pipe M.T 504.90 9497.17 18.81 27 50 mm dia G.I pipe 4922.78 504.90 9.75 M.T 28 40 mm dia G.I pipe 403.92 504.90 M.T 0.80 29 25 mm dia G.I pipe 2150.87 504.90 M.T 4.26 30 20 mm dia G.I pipe P/F C.I double acting air valve of approved quality with bolts, nuts, rubber insertions 61765.80 No 5147.15 12.00 complete (The tail pieces, tapers etc. if required will be paid separately): 50mm dia 31 Fabrication and Providing and fixing of MS Flanged bends, Tee's etc at required spots 60000.00 12000 No 5.00 including earthwork refilling and all carriages: 100mm dia 32 9000 45000.00 5.00 No 33 Dismantling old plaster or skirting, raking out joints and cleaning the surface for 17049.31 35.35 482.3 Sqm plaster including disposal of rubbish to the dumping ground within 50 meters lead 34 1892812.50 168.25 11250 Cum Silt clearance from canals Inclusive of initial lead & lift (50m & 1.5m respectively): Wet 1135687.50 100.95 Cum 35 11250 269457.50 414.55 Dry stone pitching, 225mm thick, including cost of stones and preparation of surface Sam 650 36 Carriage of excavated earth /rubbish to dumping site by mechanical means including 37 5494680.00 305.26 Cum 18000 loading, unloading for average lead of 10Kms complete. 38 Providing and fixing gun metal gate valve with C.I. wheel of approved quality (screwed 6275.40 1568.85 No 4.00 39 end): 65mm dia Constructing masonry Chamber of specified size, in brick work with common burnt clay (non modular) bricks of class designation 7.5 in cement mortar 1:4 (1cement :4 coarse sand) and R.C.C. top slab 1:1.5:3mix (1 cement : 1.5 coarse sand : 3 graded stone aggregate 20 mm nominal size) including necessary excavation, foundation concrete 31074.40 15537,20 1:5:10 (1 cement :5 fine sand : 10 graded stone aggregate 40 mm nominal size) and No 2.00 inside plastering with cement mortar 1:3 (1 cement : 3 coarse sand) 12 mm thick 40 finished with a floating coat of neat cement complete as per standard design: For sluice valve, with C.I. surface box 100 mm top diameter, 160 mm bottom diameter and

(Rupees One Crore Thirty Four Lacs Five Thousand Seven Hundred Seventy Two only)

13405772.3

Total: "AT PAR"

(Rates & avantity checked)

180 mm deep (inside) with chained lid. Chamber 90x90x100 cm

M

Office of the Executive Engineer, PHE (Jal Shakti) Division Chadoora ALLOTMENT LETTER (JJM)

No: PHEDC/ 5343-44

40 mm dia 6.00 Each Carriage of pipes by Mechnical transport from different source upto dumping site of work including loading, un-loading & stacking lead 30 Kms: 100 mm dia D.J pipe 13.50 M.T				Dated: 13 - 10 -2022				
work including loading, un-loading & stacking lead 30 Kms: 100 mm dia D.I pipe 13.50 mm dia G.I pipe 14.26 m.T 20mm dia G.I pipe 2000.00 Mtr including handling/rehandling complete lead 1000 mtrs: 100 mm dia D.I pipe 13.50 m.T 5 mm dia G.I pipe 13.50 m.T 6 mm dia G.I pipe 13.50 m.T 7 mm dia G.I pipe 13.50 m.T 8 mm dia G.I pipe 13.50 m.T 9 Do 20 mm dia G.I pipe 14.26 m.T 15 mm dia G.I pipe 15 mm dia G.I pipe 16 m.T 17 mm dia G.I pipe 17 m.T 18 mm dia G.I pipe 18 mm dia G.I pipe 18 mm dia G.I pipe 19 mm dia G.I pipe 10 mm dia G.I pipe 10 mm dia G.I pipe 11 m.T 12 mm dia G.I pipe 12 mm dia G.I pipe 13 mm dia G.I pipe 14 m.T 15 mm dia G.I pipe 16 m.T 17 mm dia G.I pipe 17 mm dia G.I pipe 18 mm dia G.I pipe 18 mm dia G.I pipe 19 mm dia G.I pipe 10 mm dia G.I pipe 10 mm dia G.I pipe 11 m.T 12 mm dia G.I pipe 12 mm dia G.I pipe 13 mm dia G.I pipe 14 m.T 15 mm dia G.I pipe 16 m.T 17 m.T 18 mm dia G.I pipe 17 m.T 18 mm dia G.I pipe 18 mm dia G.I pipe 19 mm dia G.I pipe 10 mm dia G.I pipe 10 mm dia G.I pipe 11 m.T 12 mm dia G.I pipe 12 mm dia G.I pipe 13 mm dia G.I pipe 14 m.T 15 mm dia G.I pipe 15 m.T 16 m.T 17 m.T 18 mm dia G.I pipe 18 m.T 18 mm dia G.I pipe 19 m.T 10 mm dia G.I pipe 10 m.T 10 mm dia G.I pipe 10 m.T 11 m.T 12 mm dia G.I pipe 11 m.T 12 mm dia G.I pipe 12 mm dia G.I pipe 13 mm dia G.I pipe 14 m.T 15 mm dia G.I pipe 15 m.T 16 mm dia G.I pipe 16 m.T 17 m.T 18 mm dia G.I pipe 18 m.T 18 mm dia G.I pipe 19 m.T 10 mm dia G.I pipe	-	40 mm dia		_	617.80	3706.80		
1 So mm dia G.I pipe 2 So mm dia G.I pipe 2 So mm dia G.I pipe 3 So mm dia G.I pipe 4 So mm dia G.I pipe 4 So mm dia G.I pipe 5 So mm dia G.I pipe 5 So mm dia G.I pipe 1 So mm dia G.I pipe 2 So mm dia G.I pipe 3 So mm dia G.I pipe 4 So mm dia G.I pipe 5 So mm dia G.I pipe 7 So mm dia G.I pipe 9 So mm dia g.I pipe 1 So mm d	19	Carriage of pipes by Mechnical transport from different source upto dumping site of work including loading, un-loading & stacking lead 30 Kms: 100 mm dia D.I pipe	2000.00	Mtr	9.20	18400.00		
40 mm dia G.I pipe 25 mm dia G.I pipe 20 mm dia G.I pipe 30 md dia G.I pipe 30 md dia G.I pipe 31 carriage of pipes from Dumping site to actual site of work by manual labour / ponies including handling/rehandling complete lead 1000 mtrs: 100 mm dia D.I pipe 30 mm dia G.I pipe 31 de mm dia G.I pipe 32 de mm dia G.I pipe 33 de mm dia G.I pipe 34 de mm dia G.I pipe 35 de mm dia G.I pipe 36 de mm dia G.I pipe 37 de mm dia G.I pipe 38 de mm dia G.I pipe 39 de mm dia G.I pipe 40 de mm dia G.I pipe 41 de mm dia G.I pipe 42 de mm dia G.I pipe 43 de mm dia G.I pipe 44 de mm dia G.I pipe 45 de mm dia G.I pipe 46 de mm dia G.I pipe 47 de mm dia G.I pipe 48 de mm dia G.I pipe 48 de mm dia G.I pipe 59 de mm dia G.I pipe 40 de mm dia G.I pipe 40 de mm dia G.I pipe 41 de mm dia G.I pipe 42 de mm dia G.I pipe 43 de mm dia G.I pipe 44 de mm dia G.I pipe 54 de mm dia G.I pipe 55 de mm dia G.I pipe 66 de mm dia G.I pipe 76 de mm dia G.I pipe 77 de mm dia G.I pipe 78 de mm dia G.I pipe 89 de mm dia G.I pipe 90 de mm dia G.I pipe 10 de mm dia G.I pipe 11 de mm dia G.I pipe 12 de mm dia G.I pipe 12 de mm dia G.I pipe 13 de mm dia G.I pipe 14 de mm dia G.I pipe 15 de mm dia G.I pipe 16 de mm dia G.I pipe 17 de mm dia G.I pipe 18 de mm dia G	20	65 mm dia G.1 pipe	13.50	M.T	387.87	5236.25		
25 mm dia G.I pipe 200 mm dia G.I pipe 300 mm dia G.I pipe 4.26 M.T 300 mm dia G.I pipe 50 Carriage of pipes from Dumping site to actual site of work by manual labour / ponies including handling/rehandling complete lead 1000 mtrs: 100 mm dia D.I pipe 51 50 mm dia G.I pipe 52 50 mm dia G.I pipe 53 50 mm dia G.I pipe 54 50 mm dia G.I pipe 55 65 mm dia G.I pipe 66 55 mm dia G.I pipe 76 50 mm dia G.I pipe 77 50 mm dia G.I pipe 78 50 mm dia G.I pipe 79 50 mm dia G.I pipe 70 50 mm dia G.I pipe 71 50 mm dia G.I pipe 72 50 mm dia G.I pipe 73 50 mm dia G.I pipe 74 50 mm dia G.I pipe 75 60 0.80 M.T 61 50 f. Complete (The tail pieces, tapers etc. if required will be paid separately): 50mm dia 12.00 No 12	21	50 mm dia G.I pipe	18.81	M.T	387.87	7295.83		
25 mm dia G.I pipe 200 mm dia G.I pipe 300 mm dia G.I pipe 4.26 M.T 300 mm dia G.I pipe 50 Carriage of pipes from Dumping site to actual site of work by manual labour / ponies including handling/rehandling complete lead 1000 mtrs: 100 mm dia D.I pipe 51 50 mm dia G.I pipe 52 50 mm dia G.I pipe 53 50 mm dia G.I pipe 54 50 mm dia G.I pipe 55 65 mm dia G.I pipe 66 55 mm dia G.I pipe 76 50 mm dia G.I pipe 77 50 mm dia G.I pipe 78 50 mm dia G.I pipe 79 50 mm dia G.I pipe 70 50 mm dia G.I pipe 71 50 mm dia G.I pipe 72 50 mm dia G.I pipe 73 50 mm dia G.I pipe 74 50 mm dia G.I pipe 75 60 0.80 M.T 61 50 f. Complete (The tail pieces, tapers etc. if required will be paid separately): 50mm dia 12.00 No 12	22	40 mm dia G.I pipe	9.75	M.T	387.87	3781.73		
Carriage of pipes from Dumping site to actual site of work by manual labour / ponies including handling/rehandling complete lead 1000 mtrs: 100 mm dia D.I pipe 5	23	25 mm dia G.I pipe	0.80	M.T	387.87	310.30		
including handling/rehandling complete lead 1000 mtrs: 100 mm dia D.I pipe 55 mm dia G.I pipe 13.50 M.T 50 mm dia G.I pipe 9.75 M.T 9 25 mm dia G.I pipe 9.75 M.T 10 20 mm dia G.I pipe 12.00 No 12 20 mm dia G.I pipe 12.00 No 12 20 mm dia G.I pipe 13.50 M.T 14.26 M.T 15 20 mm dia G.I pipe 16 30 No 17 20 mm dia G.I pipe 17 20 mm dia G.I pipe 18 25 mm dia G.I pipe 18 25 mm dia G.I pipe 19 25 mm dia G.I pipe 10 20 mm dia G.I pipe 10 20 mm dia G.I pipe 10 20 mm dia G.I pipe 11 2.00 No 12 Fobrication and Providing and fixing of MS Flanged bends, ree's etc at required spots including earthwork refilling and all carriages: 100mm dia 18 80mm dia 19 Dismantling old plaster or skirting, raking out joints and cleaning the surface for plaster including disposal of rubbish to the dumping ground within 50 meters lead 18 Silt clearance from canals Inclusive of initial lead & lift (50m & 1.5m respectively): Wet 10 20 mm dia G.I pipe 11 2.00 No 12 20 mm dia G.I pipe 12 30 No 13 80mm dia 12 30 No 13 80mm dia 14 Dismantling old plaster or skirting, raking out joints and cleaning the surface for plaster including disposal of rubbish to the dumping ground within 50 meters lead 18 5.00 No 18 6.00 No 18 6.00 No 18 7 Dry stone pitching, 225mm thick, including cost of stones and preparation of surface 10 Dry stone pitching, 225mm thick, including cost of stones and preparation of surface 12 Carriage of excavated earth /rubbish to dumping site by mechanical means including loading, unloading for average lead of 10Kms complete. 18 9 Providing and fixing gun metal gate valve with C.I. wheel of approved quality (screwed end): 650 Sqm 18 00 No 1	24	20 mm dia G.I pipe	4.26	M.T	387.87	1652.33		
5 65 mm dia G.I pipe 13.50 M.T 7 50 mm dia G.I pipe 9,75 M.T 8 40 mm dia G.I pipe 9,75 M.T 9 25 mm dia G.I pipe 9,75 M.T 10 20 mm dia G.I pipe 9,75 M.T 11 P/F C.I double acting air valve of approved quality with bolts, nuts, rubber insertions complete (The tail pieces, tapers etc. if required will be paid separately): 50mm dia 1 Fabrication and Providing and fixing of MS Flanged bends, Tee's etc at required spots including earthwork refilling and all carriages: 100mm dia 1 Dismantling old plaster or skirting, raking out joints and cleaning the surface for plaster including disposal of rubbish to the dumping ground within 50 meters lead 1 Dismantling old plaster or skirting, raking out joints and cleaning the surface for plaster including disposal of rubbish to the dumping ground within 50 meters lead 2 Silt clearance from canals Inclusive of initial lead & lift (50m & 1.5m respectively): Wet 3 Dry stone pitching, 225mm thick, including cost of stones and preparation of surface 3 Dry 3 Dry stone pitching, 225mm thick, including cost of stones and preparation of surface 4 Carriage of excavated earth /rubbish to dumping site by mechanical means including loading, unloading for average lead of 10Kms complete. 4 Providing and fixing gun metal gate valve with C.I. wheel of approved quality (screwed end): 65mm dia 4 Constructing masonry Chamber of specified size, in brick work with common burnt clay (non modular) bricks of class designation 7.5 in cement mortar 1:4 (1cement :4 coarse sand) and R.C.C. top slab 1:1.5:3mix (1 cement : 1.5 coarse sand : 3 graded stone aggregate 20 mm nominal size) including necessary excavation, foundation concrete sand) and R.C.C. top slab 1:1.5:3mix (1 cement : 1.5 coarse sand) 12 mm thick (finished with a floating coat of neat cement complete as per standard design: For sluice valve, with C.I. surface box 100 mm top diameter, 160 mm bottom diameter and 180 mm deep (inside) with chained lid. Chamber 90x90x100 cm	25	그러 보고 있다면 그리고 하다면 가게 있다면 가는 그는 바다에 가는 그리고 있다면 그리고 그리고 있다면 그래도 그리고 있는데 그리고 있다면 없는데 그리고 있다.	2000.00	Mtr	13.64	27280.00		
7 50 mm dia G.I pipe 7 40 mm dia G.I pipe 8 40 mm dia G.I pipe 9 75 M.T 9 25 mm dia G.I pipe 9 75 M.T 9 25 mm dia G.I pipe 9 75 M.T 10 20 mm dia G.I pipe 11 P/F C.I double acting air valve of approved quality with bolts, nuts, rubber insertions complete (The tail pieces, tapers etc. if required will be paid separately): 50mm dia 12 Fabrication and Providing and fixing of MS Flanged bends, Tee's etc at required spots including earthwork refilling and all carriages: 100mm dia 13 80mm dia 14 Dismantling old plaster or skirting, raking out joints and cleaning the surface for plaster including disposal of rubbish to the dumping ground within 50 meters lead 14 Dismantling old plaster of skirting, raking out joints and cleaning the surface for plaster including disposal of rubbish to the dumping ground within 50 meters lead 15 Silt clearance from canals Inclusive of initial lead & lift (50m & 1.5m respectively): Wet 11250 Cum 16 Dry 17 Cum 11250 Cum 18 Carriage of excavated earth /rubbish to dumping site by mechanical means including loading, unloading for average lead of 10Kms complete. 18 Providing and fixing gun metal gate valve with C.I. wheel of approved quality (screwed end): 65mm dia 18 Constructing masonry Chamber of specified size, in brick work with common burnt clay (non modular) bricks of class designation 7.5 in cement mortar 1:4 (1cement :4 coarse sand) and R.C.C top slab 1:1.5:3mix (1 cement : 1.5 coarse sand) : 3 graded stone aggregate 20 mm nominal size) including necessary excavation, foundation concrete and inside plastering with cement mortar 1:3 (1 cement : 3 coarse sand) 12 mm thick finished with a floating coat of neat cement complete as per standard design: For sluice valve, with C.I. surface box 100 mm top diameter, 160 mm bottom diameter and 180 mm deep (inside) with chained lid. Chamber 90x90x100 cm	26	The same of the sa	13.50	M.T	504.90	6816.15		
40 mm dia G.I pipe 9.75 M.T 9 25 mm dia G.I pipe 0.80 M.T 1 20 mm dia G.I pipe 2 20 mm dia G.I pipe 1 20 mm dia G.I pipe 2 3 mm dia G.I pipe 2 4.26 M.T 3 phy F. C.I double acting air valve of approved quality with bolts, nuts, rubber insertions complete (The tail pieces, tapers etc. if required will be paid separately): 50mm dia 2 Fabrication and Providing and fixing of MS Flanged bends, Tee's etc at required spots including earthwork refilling and all carriages: 100mm dia 3 80mm dia 4 Dismantling old plaster or skirting, raking out joints and cleaning the surface for plaster including disposal of rubbish to the dumping ground within 50 meters lead 3 Sit clearance from canals Inclusive of initial lead & lift (50m & 1.5m respectively): Wet plaster including disposal of rubbish to the dumping steep with 11250 Cum pry 3 Dry stone pitching, 225mm thick, including cost of stones and preparation of surface plastering of excavated earth /rubbish to dumping site by mechanical means including leading, unloading for average lead of 10Kms complete. 3 Providing and fixing gun metal gate valve with C.I. wheel of approved quality (screwed end): 65mm dia 4 Constructing masonry Chamber of specified size, in brick work with common burnt clay (non modular) bricks of class designation 7.5 in cement mortar 1:4 (1cement :4 coarse sand) and R.C.C. top slab 1:1.5:3mix (1 cement : 1.5 coarse sand): 3 graded stone aggregate 20 mm nominal size) and inside plastering with cement mortar 1:3 (1 cement : 3 coarse sand): 12 mm thick finished with a floating coat of neat cement complete as per standard design: For sluice valve, with C.I. surface box 100 mm top diameter, 160 mm bottom diameter and 180 mm deep (inside) with chained lid. Chamber 90x90x100 cm	27		18.81	M.T	504.90	9497.17		
25 mm dia G.I pipe 20 mm dia G.I pipe 4.26 M.T 21 P/F C.I double acting air valve of approved quality with bolts, nuts, rubber insertions complete (The tail pieces, tapers etc. if required will be paid separately): 50mm dia 2 Fabrication and Providing and fixing of MS Flanged bends, Tee's etc at required spots including earthwork refilling and all carriages: 100mm dia 38 80mm dia 40 Dismantling old plaster or skirting, raking out joints and cleaning the surface for plaster including disposal of rubbish to the dumping ground within 50 meters lead 35 Silt clearance from canals Inclusive of initial lead & lift (50m & 1.5m respectively): Wet 36 Dry 37 Dry stone pitching, 225mm thick, including cost of stones and preparation of surface 38 Carriage of excavated earth /rubbish to dumping site by mechanical means including loading, unloading for average lead of 10Kms complete. 39 Providing and fixing gun metal gate valve with C.I. wheel of approved quality (screwed end): 65mm dia 39 Constructing masonry Chamber of specified size, in brick work with common burnt clay (non modular) bricks of class designation 7.5 in cement mortar 1:4 (1cement :4 coarse sand) and R.C.C top slab 1:1.5:3mix (1 cement : 1.5 coarse sand : 3 gragegate 20 mm nominal size) including necessary excavation, foundation concrete aggregate 20 mm nominal size) in graded stone aggregate 40 mm nominal size) and inside plastering with cement mortar 1:3 (1 cement : 3 coarse sand) 12 mm thick finished with a floating coat of neat cement complete as per standard design: For sluice valve, with C.I. surface box 100 mm top diameter, 160 mm bottom diameter and 180 mm deep (inside) with chained lid. Chamber 90x90x100 cm Total: "	28		9.75	M.T	504.90	4922.78		
20 20 mm dia G.I pipe P/F C.I double acting air valve of approved quality with bolts, nuts, rubber insertions complete (The tail pieces, tapers etc. if required will be paid separately): 50mm dia Fabrication and Providing and fixing of MS Flanged bends, Tee's etc at required spots including earthwork refilling and all carriages: 100mm dia 80mm dia Dismantling old plaster or skirting, raking out joints and cleaning the surface for plaster including disposal of rubbish to the dumping ground within 50 meters lead Dry Silt clearance from canals Inclusive of initial lead & lift (50m & 1.5m respectively): Wet Tory stone pitching, 225mm thick, including cost of stones and preparation of surface Carriage of excavated earth /rubbish to dumping site by mechanical means including loading, unloading for average lead of 10Kms complete. Providing and fixing gun metal gate valve with C.I. wheel of approved quality (screwed end): 65mm dia Constructing masonry Chamber of specified size, in brick work with common burnt clay (non modular) bricks of class designation 7.5 in cement mortar 1:4 (1cement :4 coarse sand) and R.C.C top slab 1:1.5:3mix (1 cement : 1.5 coarse sand : 3 graded stone aggregate 20 mm nominal size) and inside plastering with cement mortar 1:3 (1 cement : 3 coarse sand) 12 mm thick finished with a floating coat of neat cement complete as per standard design: For sluice valve, with C.I. surface box 100 mm top diameter, 160 mm bottom diameter and 180 mm deep (inside) with chained lid. Chamber 90x90x100 cm Total: " Total: "	29		0.80	M.T	504.90	403.92		
P/F C.I double acting air valve of approved quality with bolts, nuts, rubber insertions complete (The tail pieces, tapers etc. if required will be paid separately): 50mm dia Fabrication and Providing and fixing of MS Flanged bends, Tee's etc at required spots including earthwork refilling and all carriages: 100mm dia Dismantling old plaster or skirting, raking out joints and cleaning the surface for plaster including disposal of rubbish to the dumping ground within 50 meters lead plaster including disposal of rubbish to the dumping ground within 50 meters lead plaster including disposal of rubbish to the dumping ground within 50 meters lead plaster including disposal of rubbish to the dumping site by methanical means including 11250 Cum 11250 C	30		4.26	M.T	504.90	2150.87		
Fabrication and Providing and fixing of MS Flanged bends, Tee's etc at required spots including earthwork refilling and all carriages: 100mm dia Somm dia Dismantling old plaster or skirting, raking out joints and cleaning the surface for plaster including disposal of rubbish to the dumping ground within 50 meters lead Formula including disposal of rubbish to the dumping ground within 50 meters lead Formula including disposal of rubbish to the dumping ground within 50 meters lead Formula including disposal of rubbish to the dumping ground within 50 meters lead Formula including disposal of rubbish to the dumping ground within 50 meters lead Formula including disposal of rubbish to the dumping ground within 50 meters lead Formula including disposal of rubbish to the dumping ground within 50 meters lead Formula including disposal of rubbish to the dumping ground within 50 meters lead Formula including disposal of rubbish to the dumping ground within 50 meters lead Formula including disposal of rubbish to the dumping ground within 50 meters lead Formula including disposal of rubbish to the dumping ground within 50 meters lead Formula including disposal of rubbish to the dumping ground within 50 meters lead Formula including disposal of rubbish to the dumping ground within 50 meters lead Formula including disposal of rubbish to the dumping ground within 50 meters lead Formula including disposal of rubbish to the dumping ground within 50 meters lead Formula including disposal of rubbish to the dumping ground within 50 meters lead Formula including dead including octation including dead i	31	P/F C.I double acting air valve of approved quality with bolts, nuts, rubber insertions	12.00	No	5147.15	61765.80		
Dismantling old plaster or skirting, raking out joints and cleaning the surface for plaster including disposal of rubbish to the dumping ground within 50 meters lead Silt clearance from canals Inclusive of initial lead & lift (50m & 1.5m respectively): Wet 11250 Cum 11250 Cu	32	Fabrication and Providing and fixing of MS Flanged bends, Tee's etc at required spots	5.00	No	12000	60000.00		
Dismantling old plaster or skirting, raking out joints and cleaning the surface for plaster including disposal of rubbish to the dumping ground within 50 meters lead Silt clearance from canals Inclusive of initial lead & lift (50m & 1.5m respectively): Wet 11250 Cum 11250 Cu	33		5.00	No	9000	45000.00		
Silt clearance from canals Inclusive of initial lead & lift (50m & 1.5m respectively): Wet 11250 Cum 11250 Dry 11250 Dry 11250 Dry 11250 Cum 11250 Cum 11250 Dry stone pitching, 225mm thick, including cost of stones and preparation of surface 650 Sqm loading, unloading for average lead of 10Kms complete. Providing and fixing gun metal gate valve with C.I. wheel of approved quality (screwed end): 65mm dia Constructing masonry Chamber of specified size, in brick work with common burnt clay (non modular) bricks of class designation 7.5 in cement mortar 1:4 (1cement :4 coarse sand) and R.C.C. top slab 1:1.5:3mix (1 cement : 1.5 coarse sand : 3 graded stone aggregate 20 mm nominal size) including necessary excavation, foundation concrete 1:5:10 (1 cement :5 fine sand : 10 graded stone aggregate 40 mm nominal size) and inside plastering with cement mortar 1:3 (1 cement : 3 coarse sand) 12 mm thick finished with a floating coat of neat cement complete as per standard design: For sluice valve, with C.I. surface box 100 mm top diameter, 160 mm bottom diameter and 180 mm deep (inside) with chained lid. Chamber 90x90x100 cm	34	Dismantling old plaster or skirting, raking out joints and cleaning the surface for	482.3	Sqm	35.35	17049.31		
Dry stone pitching, 225mm thick, including cost of stones and preparation of surface Carriage of excavated earth /rubbish to dumping site by mechanical means including loading, unloading for average lead of 10Kms complete. Providing and fixing gun metal gate valve with C.I. wheel of approved quality (screwed end): 65mm dia Constructing masonry Chamber of specified size, in brick work with common burnt clay (non modular) bricks of class designation 7.5 in cement mortar 1:4 (1cement :4 coarse sand) and R.C.C. top slab 1:1.5:3mix (1 cement : 1.5 coarse sand : 3 graded stone aggregate 20 mm nominal size) including necessary excavation, foundation concrete 1:5:10 (1 cement :5 fine sand : 10 graded stone aggregate 40 mm nominal size) and inside plastering with cement mortar 1:3 (1 cement : 3 coarse sand) 12 mm thick finished with a floating coat of neat cement complete as per standard design: For sluice valve, with C.I. surface box 100 mm top diameter, 160 mm bottom diameter and 180 mm deep (inside) with chained lid. Chamber 90x90x100 cm	25	Silt clearance from canals Inclusive of initial lead & lift (50m & 1.5m respectively): Wet	11250	Cum	168.25	1892812.5		
237 Dry stone pitching, 225mm thick, including cost of stones and preparation of surface 238 Carriage of excavated earth /rubbish to dumping site by mechanical means including 239 Ioading, unloading for average lead of 10Kms complete. 239 Providing and fixing gun metal gate valve with C.I. wheel of approved quality (screwed end): 65mm dia 240 Constructing masonry Chamber of specified size, in brick work with common burnt clay (non modular) bricks of class designation 7.5 in cement mortar 1:4 (1cement :4 coarse sand) and R.C.C. top slab 1:1.5:3mix (1 cement : 1.5 coarse sand : 3 graded stone aggregate 20 mm nominal size) including necessary excavation, foundation concrete 1:5:10 (1 cement :5 fine sand : 10 graded stone aggregate 40 mm nominal size) and inside plastering with cement mortar 1:3 (1 cement : 3 coarse sand) 12 mm thick finished with a floating coat of neat cement complete as per standard design: For sluice valve, with C.I. surface box 100 mm top diameter, 160 mm bottom diameter and 180 mm deep (inside) with chained lid. Chamber 90x90x100 cm 3	_		11250	Cum	100.95	1135687.5		
Carriage of excavated earth /rubbish to dumping site by mechanical means including loading, unloading for average lead of 10Kms complete. Providing and fixing gun metal gate valve with C.I. wheel of approved quality (screwed end): 65mm dia Constructing masonry Chamber of specified size, in brick work with common burnt clay (non modular) bricks of class designation 7.5 in cement mortar 1:4 (1cement :4 coarse sand) and R.C.C. top slab 1:1.5:3mix (1 cement : 1.5 coarse sand : 3 graded stone aggregate 20 mm nominal size) including necessary excavation, foundation concrete 1:5:10 (1 cement :5 fine sand : 10 graded stone aggregate 40 mm nominal size) and inside plastering with cement mortar 1:3 (1 cement : 3 coarse sand) 12 mm thick finished with a floating coat of neat cement complete as per standard design: For sluice valve, with C.I. surface box 100 mm top diameter, 160 mm bottom diameter and 180 mm deep (inside) with chained lid. Chamber 90x90x100 cm Total: "	-	Doy stone pitching, 225mm thick, including cost of stones and preparation of surface	650	Sqm	414.55	269457.50		
Providing and fixing gun metal gate valve with C.I. wheel of approved quality (screwed end): 65mm dia Constructing masonry Chamber of specified size, in brick work with common burnt clay (non modular) bricks of class designation 7.5 in cement mortar 1:4 (1cement :4 coarse sand) and R.C.C. top slab 1:1.5:3mix (1 cement : 1.5 coarse sand : 3 graded stone aggregate 20 mm nominal size) including necessary excavation, foundation concrete 1:5:10 (1 cement :5 fine sand : 10 graded stone aggregate 40 mm nominal size) and inside plastering with cement mortar 1:3 (1 cement : 3 coarse sand) 12 mm thick finished with a floating coat of neat cement complete as per standard design: For sluice valve, with C.I. surface box 100 mm top diameter, 160 mm bottom diameter and 180 mm deep (inside) with chained lid. Chamber 90x90x100 cm Total: "	38	Carriage of excavated earth /rubbish to dumping site by mechanical means including leading uploading for average lead of 10Kms complete.	18000	Cum	305.26	5494680.00		
Constructing masonry Chamber of specified size, in brick work with common burnt clay (non modular) bricks of class designation 7.5 in cement mortar 1:4 (1cement :4 coarse sand) and R.C.C. top slab 1:1.5:3mix (1 cement : 1.5 coarse sand : 3 graded stone aggregate 20 mm nominal size) including necessary excavation, foundation concrete 1:5:10 (1 cement :5 fine sand : 10 graded stone aggregate 40 mm nominal size) and inside plastering with cement mortar 1:3 (1 cement : 3 coarse sand) 12 mm thick finished with a floating coat of neat cement complete as per standard design: For sluice valve, with C.I. surface box 100 mm top diameter, 160 mm bottom diameter and 180 mm deep (inside) with chained lid. Chamber 90x90x100 cm Total: "	39	Providing and fixing gun metal gate valve with C.I. wheel of approved quality (screwed	4.00	No	1568.85	6275.40		
	40	Constructing masonry Chamber of specified size, in brick work with common burnt clay (non modular) bricks of class designation 7.5 in cement mortar 1:4 (1cement :4 coarse sand) and R.C.C. top slab 1:1.5:3mix (1 cement : 1.5 coarse sand : 3 graded stone aggregate 20 mm nominal size) including necessary excavation, foundation concrete 1:5:10 (1 cement :5 fine sand : 10 graded stone aggregate 40 mm nominal size) and inside plastering with cement mortar 1:3 (1 cement : 3 coarse sand) 12 mm thick finished with a floating coat of neat cement complete as per standard design: For	2.00		15537.20	31074.40		
(Ruppes One Crore Thirty Four Lacs Five Thousand Seven Hundred Seventy Two Only)	-		auantu E.		ALPAN	25 10577215		
[haptes one	-	(Rupees One Crore Thirty Four Lacs Five Thousand Seven Hundred S	(Rupees One Crore Thirty Four Lacs Five Thousand Seven Hundred Seventy 1940 only)					

(Rates & quantity checked)

Head Droftspran

Executive Engineer Jal Spakti PHE Division Chadoora

Drawing Branch

Terms and conditions

Time of completion is essence of the contract.

The work shall have to be started by you at site immediately and ensure its successful comple period of 150days from the date of issuance of this allotment from this office strictly in accorda approved proposals failing which the shall have to be executed through any other means at ye cost, besides, the CDR deposited by you security against this contract shall be forfeited.

3. An agreement shall have to be drawn up by you with the department within a period of 3 days from of issuance of allotment failure to execute such a formal deed shall however prevent the contract)

enforced upon you.

The allotted works shall be subject to check by third party monitoring agency appointed by the depo 5. Payment shall be released as per actual and measured work done not less than 20% of allotted cost.

6. Performance security equivalent to 03% of the value of the contract is to be deposited by you in . CDR/FDR/Bank Guarantee valid for a period of 03 months beyond the expiry of warranty period contract.

7. The firm shall be bound for satisfactory performance of works for 03months after the succession. commissioning of the work. If during warranty period any malfunctioning/defect arises, you shall he rectify the same within a period of ten days of receipt of intimation. In case of any failure on your part, department may get the defects removed/repaired any other means and cost thereof shall be recovered, you and shall be recommended for further punitive action as governed under the relevant clause of contract including black listing.

8. After testing and commissioning of works you shall have to make a trial run of the works for a period three months during which you have to operate and maintain the executed works to the full satisfaction

9. The defect liability period shall be for a period of 12 months and shall commence after the success

completion of trail run.

10. Pre & post geo-tagged photographic evidence be taken during the execution of the work and shall have to produced at the time of submission of the bill.

11. Date of start of the work shall be reckoned with in 07days from the date of issue of the letter. However, date of start for laying and fitting of pipes will start within two days of issuance of pipe materials by th department.

12. All other terms and conditions shall be applicable as laid down in standard bidding document (SBD) and

PWD form No. 25/33.

13. Any rules/terms and conditions if not stipulated in the bidding document, shall be strictly deemed in accordance with the relevant rules/guidelines stipulated in General Financial Rule (GFR-2017) and manual for procurement of works 2019 G.O.I. 14. The agency shall adhere to and comply with orders and instructions of the Engineer in charge and Third

Party Inspection and Monitoring Agency and any other verification agency.

xecutive Engineer, hakti PHE Division Chadoora 8

Copy to the:

for Information and necessary action. 1. Asstt. Ex. Engineer Jal Shakti PHE Sub-Division He shall ensure execution of work as per JJM guidelines, monitoring by TPIMA, and observance of all relevant IS codes and Government Orders in vogue.